

## Cat5e & Cat6 Patch Panel

### Benefits

- ✓ 19" Patch Rack Panel with 1U to 4U.
- ✓ Meet ANSI/TIA/EIA-568-A, ISO/IEC 11801& EN50173
- ✓ Delta Electronics testing approved
- ✓ UL listed 9G62
- ✓ Support T568A/B wiring guideline



### Specification

19" x 1.75" (1U), 19" x 3.5" ( 2U), 19" x 5.25" (3U) and 19" x 7.0" (4U) ( Horizontal Panel ) for the 12 to 96 ports type.

19" x 1.75" (1U), 12/16/24 Ports and Mini 8 Ports type ( Vertical Type Panel ).

Dual type Terminal Block, accept Both Krone & 110 Punch tool.

110 Terminal Block, accept 110(AT&T ) Punch tool only.

Accept 22 up to 26AWG solid wire.

### Ordering code information

P L H - 5 - U - 24 - D 0 0

Example:

	1	2	3	4	5	6	7
1	Panel Type	"H" for Horizontal insertion Tool and "V" for vertical insertion Tool					
2	Catégory	"5" for Cat5e and "6" for Cat6					
3	Shielding type	"U" for Unshielded type, "S" for Shielded type and "F" for fully shielded type.					
4	Number of Ports	"24" for 24 port type or "11", "16", "32", "48", "64" or "96".					
5	Punch Tool usage	"D" for Dual type and "A" for 110 Type					
6	With or W/O Cap	"0" With Cap and "1" W/O Cap					
7	Color	"0" for Black and "1" for Ivory					